

Isolated quick connection block PE.

Isolated quick connection block PE.Earth terminal PE 21 x 4 mm² + 6 x 16 mm².



Features

Type	Fast terminal blocks
Number of terminals	21 x 4 mm² + 6 x 16 mm²
Connection	Ground
Color	Green yellow

Technical data

Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	125 °C
Work stress	400 Vac
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60998-1:2005
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Logistics and packaging

Unit EAN code	8423220094741
EAN code container	8423220094741
EAN code packaging	18423220094748
Units packaging	1
Units carton	60
Pallet Units	2880
Packaging Measurements cm	0,23x1,4x1
Packaging Measures cm	37,5x20x30
Unit weight (g)	123
Container Weight (Kg)	0,13
Packaging Weight (Kg)	7,87
Tariff code	85369010

Documentation and downloads



[Assembly instructions \(0.91MB\)](#)