



Ref. Certif. No.

ES2501-AENOR

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

BOXES AND ENCLOSURES FOR ELECTRICAL ACCESSORIES

Name and address of the applicant

PORTALAMPARAS Y ACCESORIOS SOLERA, S.A.
PI FUENTE DEL JARRO, CL VILLA DE MADRID, 53
46988 PATERNA (Valencia - Spain)

Name and address of the manufacturer

SAME AS ABOVE

Name and address of the factory

SAME AS ABOVE

Note: When more than one factory, please report on page 2

Additional Information on page 2

Ratings and principal characteristics

See references on the Annex

Trademark (if any)

SOLERA

Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

See on the Annex

Additional information (if necessary may also be reported on page 2)

Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60670-1:2015
IEC 60670-22:2003
IEC 60670-22:2013/AMD1:2015

As shown in the Test Report Ref. No. which forms part of this Certificate

CEL-0352/21-1_1 to CEL-0352/21-1_18

This CB Test Certificate is issued by the National Certification Body

AENOR INTERNACIONAL S.A.U.
CI Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2021-10-29

Signature: 
Rafael GARCÍA MEIRO
Chief Executive Officer

ANNEX TO CB CERTIFICATE N° ES2501-AENOR

CERTIFIED REFERENCES AND THEIR MAIN RATINGS

Trade Mark: SOLERA

Product: BOXES AND ENCLOSURES FOR ELECTRICAL ACCESSORIES

Type of product: JUNCTION BOX

Material: INSULATING

| Type Ref. | Installation method | Temperature during installation | Maximun temperature during casting process | Degree of protection (IP) | Dimension (mm) Breadth x High x Depth | Additional information |
|-----------|---------------------|---------------------------------|--|---------------------------|---------------------------------------|------------------------|
| 324GW | Flush | -5 °C to +60 °C | +60 °C | IP30 | 252x252x50 | Hollow partitions |
| 5314 | Flush | -5 °C to +60 °C | +60 °C | IP30 | 194x154x50 | Hollow partitions |
| 5314GW | Flush | -5 °C to +60 °C | +60 °C | IP30 | 194x154x50 | Hollow partitions |
| 5324 | Flush | -5 °C to +60 °C | +60 °C | IP30 | 252x252x50 | Hollow partitions |
| 5362 | Flush | -5 °C to +60 °C | +60 °C | IP30 | 100x100x45 | Hollow partitions |
| 5362GW | Flush | -5 °C to +60 °C | +60 °C | IP30 | 100x100x45 | Hollow partitions |
| 5363 | Flush | -5 °C to +60 °C | +60 °C | IP30 | 164x106x47 | Hollow partitions |
| 5363GW | Flush | -5 °C to +60 °C | +60 °C | IP30 | 164x106x47 | Hollow partitions |
| 5506HGW | Flush | -5 °C to +60 °C | +60 °C | IP30 | 300x500x60 | Hollow partitions |
| 5507HGW | Flush | -5 °C to +60 °C | +60 °C | IP30 | 300x500x60 | Hollow partitions |
| 5514GW | Flush | -5 °C to +60 °C | +60 °C | IP30 | Ø100x46 | Hollow partitions |
| 5515GW | Flush | -5 °C to +60 °C | +60 °C | IP30 | Ø150x46 | Hollow partitions |
| 5516GW | Flush | -5 °C to +60 °C | +60 °C | IP30 | Ø150x46 | Hollow partitions |
| 5562 | Flush | -5 °C to +60 °C | +60 °C | IP30 | 100x100x45 | Hollow partitions |
| 5562GW | Flush | -5 °C to +60 °C | +60 °C | IP30 | 100x100x45 | Hollow partitions |
| 5563 | Flush | -5 °C to +60 °C | +60 °C | IP30 | 164x106x47 | Hollow partitions |
| 5563GW | Flush | -5 °C to +60 °C | +60 °C | IP30 | 164x106x47 | Hollow partitions |
| 5635 | Flush | -5 °C to +60 °C | +60 °C | IP30 | Ø68x46 | Hollow partitions |