



ZODZ.E470267 Positioning Devices

[Page Bottom](#)

Positioning Devices

[See General Information for Positioning Devices](#)

PORTALAMPARAS Y ACCESORIOS SOLERA S.A

E470267

C/ Villa de Madrid Nº 53

CP46988 PATERNA (Valencia), SPAIN

Nonmetallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg	Bundle Diam, mm (in.)		Loop Tensile Strength, N (lbf)	Operating Temp, °C (°F)		Min Installation Temp, °C (°F)	Resistant to UV Light	Plenum Rating	ANSI/UL 94 Mtl Flame Rating
		Min	Max		Min	Max				
BR2580	21	3.0 (0.118)	14.0 (0.551)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR2580N	21	3.0 (0.118)	14.0 (0.551)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR25100	21	3.0 (0.118)	20.5 (0.807)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR25100N	21	3.0 (0.118)	20.5 (0.807)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR25100/50	21	3.0 (0.118)	20.5 (0.807)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR25100N/50	21	3.0 (0.118)	20.5 (0.807)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR25120	21	3.0 (0.118)	27.0 (1.062)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR25120N	21	3.0 (0.118)	27.0 (1.062)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR25130	21	3.0 (0.118)	27.0 (1.062)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR25130N	21	3.0 (0.118)	27.0 (1.062)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR25150	21	3.0 (0.118)	36.5 (1.437)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR25150N	21	3.0 (0.118)	36.5 (1.437)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR25160	21	3.0 (0.118)	39.8 (1.567)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR25160N	21	3.0 (0.118)	39.8 (1.567)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR25200	21	3.0 (0.118)	52.5 (2.067)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR25200N	21	3.0 (0.118)	52.5 (2.067)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR25200/50	21	3.0 (0.118)	52.5 (2.067)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR25200N/50	21	3.0 (0.118)	52.5 (2.067)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR25260	21	3.0 (0.118)	73.0 (2.874)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR25260N	21	3.0 (0.118)	73.0 (2.874)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36140	21	3.0 (0.118)	33.0 (1.299)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR36140N	21	3.0 (0.118)	33.0 (1.299)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36140/50	21	3.0 (0.118)	33.0 (1.299)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36140N/50	21	3.0 (0.118)	33.0 (1.299)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36150	21	3.0 (0.118)	36.0 (1.417)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR36150N	21	3.0 (0.118)	36.0 (1.417)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36200	21	3.0 (0.118)	52.5 (2.067)	180 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR36200N	21	3.0 (0.118)	52.5 (2.067)	180 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36250	21	3.0 (0.118)	68.0 (2.677)	180 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR36250N	21	3.0 (0.118)	68.0 (2.677)	180 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36280	21	3.0 (0.118)	78.0 (3.071)	180 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR36280N	21	3.0 (0.118)	78.0 (3.071)	180 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36300	21	3.0 (0.118)	106.0 (4.173)	180 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR36300N	21	3.0 (0.118)	106.0 (4.173)	180 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36300/50	21	3.0 (0.118)	106.0 (4.173)	180 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR36300N/50	21	3.0 (0.118)	106.0 (4.173)	180 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36370	21	3.0 (0.118)	105.0 (4.134)	180 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR36370N	21	3.0 (0.118)	105.0 (4.134)	180 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36370/50	21	3.0 (0.118)	105.0 (4.134)	180 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR36370N/50	21	3.0 (0.118)	105.0 (4.134)	180 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR46120	21	3.0 (0.118)	23.8 (0.937)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR46120N	21	3.0 (0.118)	23.8 (0.937)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2

BR46160	21	3.0 (0.118)	36.6 (1.441)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR46160N	21	3.0 (0.118)	36.6 (1.441)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48180	21	3.0 (0.118)	43.0 (1.693)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48180N	21	3.0 (0.118)	43.0 (1.693)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48200	21	3.0 (0.118)	49.5 (1.948)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48200N	21	3.0 (0.118)	49.5 (1.948)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48200G	21	3.0 (0.118)	49.5 (1.948)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48250	21	3.0 (0.118)	65.0 (2.559)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48250N	21	3.0 (0.118)	65.0 (2.559)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48250V	21	3.0 (0.118)	65.0 (2.559)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48250M	21	3.0 (0.118)	65.0 (2.559)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48280	21	3.0 (0.118)	74.8 (2.945)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48280N	21	3.0 (0.118)	74.8 (2.945)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48300	21	3.0 (0.118)	81.0 (3.188)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48300N	21	3.0 (0.118)	81.0 (3.188)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48300G	21	3.0 (0.118)	81.0 (3.188)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48310	21	3.0 (0.118)	84.0 (3.307)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48310N	21	3.0 (0.118)	84.0 (3.307)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48350	21	3.0 (0.118)	97.0 (3.818)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48350N	21	3.0 (0.118)	97.0 (3.818)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48360	21	3.0 (0.118)	97.0 (3.818)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48360N	21	3.0 (0.118)	97.0 (3.818)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48370	21	3.0 (0.118)	103.5 (4.074)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48370N	21	3.0 (0.118)	103.5 (4.074)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48380	21	3.0 (0.118)	106.7 (4.200)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48380N	21	3.0 (0.118)	106.7 (4.200)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48390	21	3.0 (0.118)	110.0 (4.330)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48390N	21	3.0 (0.118)	110.0 (4.330)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48430	21	3.0 (0.118)	122.5 (4.822)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48430N	21	3.0 (0.118)	122.5 (4.822)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48450	21	3.0 (0.118)	129.0 (5.078)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48450N	21	3.0 (0.118)	129.0 (5.078)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48500/10	21	3.0 (0.118)	145.0 (5.708)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48500N/10	21	3.0 (0.118)	145.0 (5.708)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48550/10	21	3.0 (0.118)	160.0 (6.299)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48550N/10	21	3.0 (0.118)	160.0 (6.299)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76150	21	6.0 (0.236)	23.8 (0.937)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76150N	21	6.0 (0.236)	23.8 (0.937)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76150N/50	21	6.0 (0.236)	23.8 (0.937)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76200	21	6.0 (0.236)	50.9 (2.003)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76200N	21	6.0 (0.236)	50.9 (2.003)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76250	21	6.0 (0.236)	66.8 (2.629)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76250N	21	6.0 (0.236)	66.8 (2.629)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76300	21	6.0 (0.236)	82.8 (3.259)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76300N	21	6.0 (0.236)	82.8 (3.259)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76350	21	6.0 (0.236)	98.5 (3.877)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76350N	21	6.0 (0.236)	98.5 (3.877)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76365	21	6.0 (0.236)	103.5 (4.074)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76365N	21	6.0 (0.236)	103.5 (4.074)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76365N/50	21	6.0 (0.236)	103.5 (4.074)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76380	21	6.0 (0.236)	108.0 (4.251)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76380N	21	6.0 (0.236)	108.0 (4.251)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76400	21	3.0 (0.118)	113.0 (4.448)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76400N	21	3.0 (0.118)	113.0 (4.448)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2	V-2
BR76450	21	6.0 (0.236)	130.5 (5.137)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76450N	21	6.0 (0.236)	130.5 (5.137)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76500	21	6.0 (0.236)	146.0 (5.748)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76500N	21	6.0 (0.236)	146.0 (5.748)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76540	21	6.0 (0.236)	159.0 (6.259)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2

BR76540N	21	6.0 (0.236)	159.0 (6.259)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76550	21	6.0 (0.236)	162.5 (6.397)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76550N	21	6.0 (0.236)	162.5 (6.397)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR88400	21	9.0 (0.354)	115.0 (4.527)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR88400N	21	9.0 (0.354)	115.0 (4.527)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR88450	21	9.0 (0.354)	130.5 (5.137)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR88450N	21	9.0 (0.354)	130.5 (5.137)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR88500	21	9.0 (0.354)	146.5 (5.767)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR88500N	21	9.0 (0.354)	146.5 (5.767)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR88550	21	9.0 (0.354)	163.5 (6.437)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR88550N	21	9.0 (0.354)	163.5 (6.437)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR88560	21	9.0 (0.354)	165.5 (6.515)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR88560N	21	9.0 (0.354)	165.5 (6.515)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR88610	21	9.0 (0.354)	181.5 (7.145)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR88610N	21	9.0 (0.354)	181.5 (7.145)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR88760	21	9.0 (0.354)	229.5 (9.035)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR88760N	21	9.0 (0.354)	229.5 (9.035)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR88780	21	9.0 (0.354)	235.5 (9.271)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR88780N	21	9.0 (0.354)	235.5 (9.271)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR9810	21	9.0 (0.354)	245.0 (9.645)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR9810N	21	9.0 (0.354)	245.0 (9.645)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR9920	21	9.0 (0.354)	280.0 (11.023)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR9920N	21	9.0 (0.354)	280.0 (11.023)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR91220	21	79.0 (3.110)	375.5 (14.783)	800 (175)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR91220N	21	79.0 (3.110)	375.5 (14.783)	800 (175)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR124530	21	9.0 (0.354)	156.0 (6.141)	1200 (250)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR124530N	21	9.0 (0.354)	156.0 (6.141)	1200 (250)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR124650	21	9.0 (0.354)	195.0 (7.795)	1200 (250)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR124650N	21	9.0 (0.354)	195.0 (7.795)	1200 (250)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR1241000	21	9.0 (0.354)	315.0 (12.401)	1200 (250)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR1241000N	21	9.0 (0.354)	315.0 (12.401)	1200 (250)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48920	21	3.0 (0.118)	278.0 (10.944)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48920N	21	3.0 (0.118)	278.0 (10.944)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48190	21	3.0 (0.118)	46.0 (1.811)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48190N	21	3.0 (0.118)	46.0 (1.811)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48290	21	3.0 (0.118)	78.0 (3.071)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48290N	21	3.0 (0.118)	78.0 (3.071)	220 (50)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76280	21	6.0 (0.236)	76.4 (3.007)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76280N	21	6.0 (0.236)	76.4 (3.007)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR28380	21	3.0 (0.118)	110.0 (4.331)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR28380N	21	3.0 (0.118)	110.0 (4.331)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR36180	21	3.0 (0.118)	46.0 (1.811)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR36180N	21	3.0 (0.118)	46.0 (1.811)	80 (18)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR1241000	21	9.0 (0.354)	323.0 (12.716)	1200 (250)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR1241000N	21	9.0 (0.354)	323.0 (12.716)	1200 (250)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR76750	21	6.0 (0.236)	226.0 (8.897)	550 (120)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76750N	21	6.0 (0.236)	226.0 (8.897)	550 (120)	-40 (-40)	85 (185)	-10 (14)	YES	AH-2 ##	V-2
BR48305/P	21	4.0 (0.157)	88.1 (3.468)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48380/P	21	4.0 (0.157)	111.0 (4.370)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48160/P	21	4.0 (0.157)	41.9 (1.649)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR48200/P	21	4.0 (0.157)	54.8 (2.157)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76150/T	21	10.0 (0.393)	40.3 (1.586)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76300/T	21	10.0 (0.393)	88.1 (3.468)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76200/T	21	10.0 (0.393)	55.6 (2.188)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76370/T	21	3.0 (0.118)	109.9 (4.326)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
BR76250/T	21	10.0 (0.393)	71.8 (2.826)	220 (50)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
IDBR25100	21	3.0 (0.118)	20.5 (0.807)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2
IDBR48190	21	12.5 (0.492)	50.9 (2.003)	80 (18)	-40 (-40)	85 (185)	-10 (14)	No	AH-2 ##	V-2

Fixing Devices Investigated to ANSI/UL 62275

Cat. No.	Type Dsg	Mechanical Strength, N (lbf)	Operating Temp, °C (°F)		Resistant to UV Light	Plenum Rating	ANSI/UL 94 Mtl Flame Rating
			Min	Max			
SOA1919	21	80 (18)	-40 (-40)	85 (185)	No	AH-2##	V-2
SOA1919N	21	80 (18)	-40 (-40)	85 (185)	No	AH-2##	V-2
SOA2828	21	180 (40)	-40 (-40)	85 (185)	No	AH-2##	V-2
SOA2828N	21	180 (40)	-40 (-40)	85 (185)	No	AH-2##	V-2
SOA2828/100	21	180 (40)	-40 (-40)	85 (185)	No	AH-2##	V-2

- Note: Product designation includes suffix "AH" to reflect AH-2 Plenum Rating.

Last Updated on 2015-04-16

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".