CBMM1N32

Miniature Circuit Breaker 1P+N, 32A. Breaking capacity 6kA. C curve.



Miniature Circuit Breaker 1P+N, 32A. Breaking capacity 6kA. C curve.1 module. 240V AC (50 - 60 Hz).
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)

Features

Mechanical durability	20.000 cycles
Protection type (modular)	Magnetothermic switch
No. of poles	1P + N
Modules (18 mm)	1
Neutral position	Left
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	6 kA
Fixation	35mm DIN rail
Possibility of using pin type combs	Yes
Nominal current	32A
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 ºC
Ambient operating temperature	-5 ºC ; +40 ºC
Free of halogens	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60898-1:2020
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220093126
EAN code container	8423220091641
EAN code packaging	18423220091648
Units packaging	12
Units carton	180
Pallet Units	8100
Packaging Measures cm	43x34x24
Unit weight (g)	127
Container Weight (Kg)	1,53
Packaging Weight (Kg)	23,46
Tariff code	85362010