COMBI2P40T15

Protector MCB 2x40A + surges permament. and transitory



Protector MCB 2x40A+ surge permanet and transitory. 230Vac (50 - 60 Hz). C curve. 10kA
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)

Features

No. of poles	1P + N
Modules (18 mm)	3
Neutral position	Right
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	10 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm²
Nominal current	40A
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Protection Degree (IP)	IP20
Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-20 °C ; +70 °C
Free of halogens	Yes

Regulations

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013 ; UNE-EN 50550:2012; UNE-EN 60898-1:2020
According to Regulations IEC	IEC 61643-11
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220216983
EAN code container	8423220216983
EAN code packaging	18423220216980
Units packaging	1
Units carton	20
Pallet Units	999
Packaging Measures cm	10,2x12x14
Unit weight (g)	481
Container Weight (Kg)	0,48
Packaging Weight (Kg)	10,23
Tariff code	85362010

Documentation and downloads

Assembly instructions (0.77MB)