

MCB protector 4x25A with permanent OVP

Combined MCB protector with permanent overvoltage protection, rated at 4x25A, C curve and 10kA breaking capacity. 7-module format for 400V AC installations (50/60 Hz).



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of poles	4P
Modules (18 mm)	7
Neutral position	Right
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	10 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm ²
Nominal current	25A
Nominal voltage	400 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-20 °C ; +70 °C

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013 ; UNE-EN 50550:2012; UNE-EN 60898-1:2020
According to Regulations IEC	IEC 61643-11

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
--	-----

According to European Directive 2014/35 / EU. Low voltage directive	Yes
---	-----

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
---	-----

According to European Directive 2012/19/UE (RAEE2)	Yes
--	-----

According to Regulations (RoHS)	UNE-EN IEC 63000:2022
---------------------------------	-----------------------

Logistics and packaging

Unit EAN code	8423220289673
---------------	---------------

EAN code container	8423220289673
--------------------	---------------

EAN code packaging	18423220289670
--------------------	----------------

Units packaging	1
-----------------	---

Units carton	1
--------------	---

Pallet Units	1
--------------	---

Packaging Measures cm	47x35x18
-----------------------	----------

Unit weight (g)	1710,8
-----------------	--------

Container Weight (Kg)	1,7108
-----------------------	--------

Packaging Weight (Kg)	2,4308
-----------------------	--------

Tariff code	85362010
-------------	----------

Documentation and downloads



Safety Information (0.38MB)