S24LSP44010

4P 40A Miniature Circuit Breaker + OVT Coil

Combined MCB protector with an overvoltage trip coil (OVT), rated at 4x40A, C curve and 10kA breaking capacity. 7-module format for 400V AC installations (50/60 Hz).

Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of poles	4P
Modules (18 mm)	7
Neutral position	Right
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	10 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm²
Nominal current	40A
Nominal voltage	400 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-20 °C ; +70 °C

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013 ; UNE-EN 50550:2012; UNE-EN 60898-1:2020
According to Regulations IEC	IEC 61643-11
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes

According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220289680
EAN code container	8423220289680
EAN code packaging	18423220289687
Units packaging	1
Units carton	1
Pallet Units	1
Packaging Measures cm	47x35x18
Unit weight (g)	1710,8
Container Weight (Kg)	1,7108
Packaging Weight (Kg)	2,4308
Tariff code	85362010

Documentation and downloads

Safety Information (0.38MB)