S24LSTP240

2P 40A MCB + maximum voltage coil + SPD



Combined MCB protector with a maximum voltage coil and a surge protective device (SPD) against transient overvoltages, rated at 2x40A, C curve and 10kA breaking capacity. 4-module format for 230V AC installations (50/60 Hz).

Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of poles	2P
Modules (18 mm)	4
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	10 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm²
Nominal current	40A
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-20 °C ; +70 °C

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013 ; UNE-EN 50550:2012; UNE-EN 60898-1:2020

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

According to Regulations IEC	IEC 61643-11
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220283060
EAN code container	8423220283060
EAN code packaging	18423220283067
Units packaging	1
Units carton	30
Pallet Units	1200
Packaging Measurements cm	15x0,8x0,8
Packaging Measures cm	41x23x27
Unit weight (g)	456,8
Container Weight (Kg)	0,4882
Packaging Weight (Kg)	14,69412
Tariff code	85362010

Documentation and downloads

Assembly instructions (0.95MB)

Safety Information (0.38MB)