

MCB protector 4x25A with permanent and transient OVP

Combined MCB protector with permanent and transient overvoltage protection, rated at 4x25A, C curve and 10kA breaking capacity. 9-module format for 400V AC installations (50/60 Hz).



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of poles	4P
Modules (18 mm)	9
Neutral position	Right
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	10 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm ²
Nominal current	25A
Nominal voltage	400 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-20 °C ; +70 °C

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013 ; UNE-EN 50550:2012; UNE-EN 60898-1:2020

According to Regulations IEC	IEC 61643-11
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220283077
EAN code container	8423220283077
EAN code packaging	18423220283074
Units packaging	1
Units carton	20
Pallet Units	1000
Packaging Measurements cm	16,5x11x8,5
Packaging Measures cm	43x35x25
Unit weight (g)	985,2
Container Weight (Kg)	1,0384
Packaging Weight (Kg)	20,8465
Tariff code	85362010

Documentation and downloads



[Assembly instructions \(1.03MB\)](#)



[Safety Information \(0.38MB\)](#)