

Disconnect fuse holder. Size 2.

Size 2 switch-disconnect fuse holder for 22 × 58 mm cylindrical fuses. Single-pole (1 P) device rated 690 V AC/DC and up to 125 A. The removable cartridge functions as a load-break switch, providing safe circuit isolation during service operations. Made of self-extinguishing thermoplastic, it features IP20 finger-safe screw terminals and snap-on DIN 35 mm rail mounting, offering a rugged, fast-replacement solution for distribution boards and high-power industrial equipment.



Features

Common applications	Industrial environments (factories, warehouses, etc.)
Protection type (modular)	Fuse holder
No. of poles	1P
Network type	Alternating current (ac)
Short circuit capacity	20kA
Fixation	35mm DIN rail
Fuse size	Size 2 (22x58 mm)
Nominal current	125A
Nominal voltage	690 Vca (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
------------	-----

UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60269-1:2008
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220216952
EAN code container	8423220216945
EAN code packaging	18423220216942
Units packaging	6
Units carton	96
Pallet Units	2592
Packaging Measurements cm	16,5x10,5x7,5
Packaging Measures cm	42x34,5x31
Unit weight (g)	180
Container Weight (Kg)	1,1236
Packaging Weight (Kg)	18,5776
Tariff code	85362010

Documentation and downloads

 Assembly instructions (0.9MB)

 Safety Information (0.38MB)