

Cylindrical fuses Ø 5 x 20 mm. 10A

Glass cylindrical fuses Ø 5 x 20 mm. 10A 250V



Features

Common applications	Industrial environment
Element type	Crystal fuse
No. of poles	1P
Network type	Alternating current (ac)
Short circuit capacity	120 kA
Fuse size	Ø5 x 20 mm
Nominal current	10A
Nominal voltage	230/400 Vca - (50/60 Hz)
Additional dimensions (mm)	SV000330

Technical data

Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes

According to Regulations UNE/EN	UNE-EN 60269-1:2008
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN 63000:2018

Logistics and packaging

Unit EAN code	8423220001701
EAN code container	8423220001701
EAN code packaging	18423220001708
Tariff code	85362010

Sketch



