

Cylindrical fuses Ø 5 x 20 mm. 4A

Glass cylindrical fuses Ø 5 x 20 mm. 4A 250V



Features

Common applications	Industrial environment
Element type	Crystal fuse
No. of poles	1P
Network type	Alternating current (ac)
Short circuit capacity	120 kA
Fuse size	Ø5 x 20 mm
Nominal current	4A
Nominal voltage	230/400 Vca - (50/60 Hz)
Additional dimensions (mm)	SV000330

Technical data

Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes

According to Regulations UNE/EN	UNE-EN 60269-1:2008
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN 63000:2018

Logistics and packaging

Unit EAN code	8423220001688
EAN code container	8423220001688
EAN code packaging	18423220001685
Units packaging	100
Units carton	10000
Pallet Units	99999
Packaging Measurements cm	0,8x0,24x0,56
Packaging Measures cm	40x31,5x26
Unit weight (g)	1
Container Weight (Kg)	0,11
Packaging Weight (Kg)	11,24
Tariff code	85362010

Sketch





