

Disconnect fuse holder. Size O.

Size O switch-disconnect fuse holder for 10 × 38 mm cylindrical fuses. Single-pole (1P) device rated at 500 V AC/DC and up to 32 A. The removable cartridge acts as a load-break switch, providing safe circuit isolation for maintenance. IP20 finger-safe screw terminals and snap-on DIN 35 mm rail mounting ensure quick installation in control panels, distribution boards and machinery where dependable fuse protection and easy replacement are required.



Features

Common applications	Industrial environments (factories, warehouses, etc.)
Protection type (modular)	Fuse holder
No. of poles	1P
Modules (18 mm)	1
Network type	Alternating current (ac)
Short circuit capacity	20kA
Fixation	35mm DIN rail
Fuse size	Size O (10x38 mm)
Nominal current	32A
Nominal voltage	690 Vca (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
------------	-----

UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60269-1:2008
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220073869
EAN code container	8423220077324
EAN code packaging	18423220077321
Units packaging	12
Units carton	300
Pallet Units	9000
Packaging Measurements cm	23x8x8
Packaging Measures cm	46x24,5x35,5
Unit weight (g)	56,6
Container Weight (Kg)	0,6872
Packaging Weight (Kg)	14,319
Tariff code	85362010

Documentation and downloads



[Assembly instructions \(0.9MB\)](#)



[Safety Information \(0.38MB\)](#)