

Disconnect fuse holder. Size 1.

Size 1 switch-disconnect fuse holder for 14 × 51 mm cylindrical fuses. Single-pole (1P) device rated at 690 V AC/DC and up to 50 A. The removable cartridge serves as a load-break switch, ensuring safe circuit isolation during maintenance. IP20 finger-safe screw terminals and snap-on DIN 35 mm rail mounting allow quick installation in control panels and industrial machinery requiring dependable fuse protection and fast replacement.



Features

Common applications	Industrial environments (factories, warehouses, etc.)
Protection type (modular)	Fuse holder
No. of poles	1P
Network type	Alternating current (ac)
Short circuit capacity	20kA
Fixation	35mm DIN rail
Fuse size	Size 1 (14x51 mm)
Nominal current	50A
Nominal voltage	690 Vca (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes

CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60269-1:2008
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220073876
EAN code container	8423220077331
EAN code packaging	18423220077338
Units packaging	6
Units carton	192
Pallet Units	7680
Packaging Measurements cm	16,5x10,5x7,5
Packaging Measures cm	42x34,5x31
Unit weight (g)	106
Container Weight (Kg)	0,6796
Packaging Weight (Kg)	22,3472
Tariff code	85362010

Documentation and downloads



[Assembly instructions \(0.9MB\)](#)



[Safety Information \(0.38MB\)](#)