

## Protector MCB 2x25A + surges permanent. and transitory

Protector MCB 2x25A+ surge permanent and transitory. 230Vac (50 - 60 Hz). C curve. 10kA



### Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of poles	1P + N
Modules (18 mm)	4
Neutral position	Right
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	10 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm <sup>2</sup>
Nominal current	25A
Nominal voltage	230 Vca - (50/60 Hz)

### Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-20 °C ; +70 °C
Free of halogens	Yes

### Regulations

CE marking	Yes
------------	-----

UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013 ; UNE-EN 50550:2012; UNE-EN 60898-1:2020
According to Regulations IEC	IEC 61643-11
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

## Logistics and packaging

Unit EAN code	8423220216976
EAN code container	8423220216976
EAN code packaging	18423220216973
Units packaging	1
Units carton	20
Pallet Units	999
Packaging Measures cm	10,2x14x12
Unit weight (g)	101,5
Container Weight (Kg)	0,1015
Packaging Weight (Kg)	2,639
Tariff code	85362010

## Documentation and downloads



Safety Information (0.38MB)