

Permanent surge protection

Permanent surge protection 3P+N 400V AC (50 - 60 Hz) 3 modules



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Protection type (modular)	Permanent surge protector
No. of poles	3P + N
Modules (18 mm)	3
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Nominal voltage	400 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 50550:2012

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
--	-----

According to European Directive 2014/35 / EU. Low voltage directive	Yes
---	-----

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
---	-----

According to European Directive 2012/19/UE (RAEE2)	Yes
--	-----

According to Regulations (RoHS)	UNE-EN IEC 63000:2022
---------------------------------	-----------------------

Logistics and packaging

Unit EAN code	8423220093836
---------------	---------------

EAN code container	8423220093843
--------------------	---------------

EAN code packaging	18423220093840
--------------------	----------------

Units packaging	3
-----------------	---

Units carton	60
--------------	----

Pallet Units	99999
--------------	-------

Packaging Measurements cm	10,8x8,8x7,5
---------------------------	--------------

Packaging Measures cm	10,2x14x12
-----------------------	------------

Unit weight (g)	158
-----------------	-----

Container Weight (Kg)	0,51
-----------------------	------

Packaging Weight (Kg)	10,809
-----------------------	--------

Tariff code	85362010
-------------	----------

Documentation and downloads



Safety Information (0.38MB)