

Miniature circuit breaker 4P 6A 10kA C curve

Miniature circuit breaker 4P for residential and tertiary installations, rated at 6A, with 10kA breaking capacity and C curve. 4-module format for 400V AC networks at 50/60Hz.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanical durability	20.000 cycles
Protection type (modular)	Magnetothermic switch
No. of poles	4P
Modules (18 mm)	4
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	10 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm²
Possibility of using pin type combs	Yes
Nominal current	6A
Nominal voltage	400 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60898-1:2020 (versión corregida Febrero 2024).
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
AENOR certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220287709
EAN code container	8423220287266
EAN code packaging	18423220287263
Units packaging	3
Units carton	30
Tariff code	85362010

Documentation and downloads

 Assembly instructions (0.26MB)

 Safety Information (0.38MB)