

Miniature Circuit Breaker 1P+N, 32A. Breaking capacity 3kA. C curve.

Miniature Circuit Breaker 1P+N, 32A. Breaking capacity 3kA. C curve. 2 modules. 230Vac (50 - 60 Hz).



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanical durability	20.000 cycles
Protection type (modular)	Magnetothermic switch
No. of poles	1P + N
Modules (18 mm)	2
Neutral position	Left
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	3 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm ²
Possibility of using pin type combs	Yes
Nominal current	32A
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60898-1:2020 (versión corregida Febrero 2024).
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
AENOR certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220274112
EAN code container	8423220290495
EAN code packaging	18423220290492
Units packaging	6
Units carton	60
Pallet Units	1000
Packaging Measurements cm	22x8,5x8
Packaging Measures cm	47x24x18
Unit weight (g)	175
Container Weight (Kg)	1,1
Packaging Weight (Kg)	11,345
Tariff code	85362010

Documentation and downloads



Assembly instructions (0.26MB)



Safety Information (0.38MB)