

## Miniature Circuit Breaker 1P, 63A. Breaking capacity 6kA. C curve.

Miniature Circuit Breaker 1P, 63A. Breaking capacity 6kA. C curve. 1 module.  
230/400V AC (50 - 60 Hz).



### Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanical durability	20.000 cycles
Protection type (modular)	Magnetothermic switch
No. of poles	1P
Modules (18 mm)	1
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	6 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm <sup>2</sup>
Possibility of using pin type combs	Yes
Nominal current	63A
Nominal voltage	230/400 Vca - (50/60 Hz)

### Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

## Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60898-1:2020 (versión corregida Febrero 2024).
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
AENOR certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

## Logistics and packaging

Unit EAN code	8423220286726
EAN code container	8423220286467
EAN code packaging	18423220286464
Units packaging	12
Units carton	120
Pallet Units	6000
Packaging Measurements cm	22x8,5x8
Packaging Measures cm	47x24x18
Unit weight (g)	94,6
Container Weight (Kg)	1,1852
Packaging Weight (Kg)	12,3154
Tariff code	85362010

## Documentation and downloads



Assembly instructions (0.26MB)



Safety Information (0.38MB)