

Miniature Circuit Breaker 3P, 10A. Breaking capacity 6kA. C curve.

Miniature Circuit Breaker 3P, 10A. Breaking capacity 6 kA. C curve. 3 modules.
400 VCA (50 - 60 Hz).



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanical durability	20.000 cycles
Protection type (modular)	Magnetothermic switch
No. of poles	3P
Modules (18 mm)	3
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	6 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm ²
Possibility of using pin type combs	Yes
Nominal current	10A
Nominal voltage	400 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60898-1:2020
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
AENOR certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220283015
EAN code container	8423220283039
EAN code packaging	18423220283036
Units packaging	4
Units carton	40
Pallet Units	3600
Packaging Measurements cm	22x8,5x8
Packaging Measures cm	47x24x18
Unit weight (g)	280
Container Weight (Kg)	1,174
Packaging Weight (Kg)	12,085
Tariff code	85362010

Documentation and downloads



Assembly instructions (0.26MB)



Safety Information (0.38MB)