

Miniature Circuit Breaker 3P, 20A. Breaking capacity 6kA. C curve.

Miniature Circuit Breaker 3P, 20A. Breaking capacity 6kA. C curve. 3 modules. 400V AC (50 - 60 Hz).



Features

| | |
|-------------------------------------|---|
| Common applications | Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.) |
| Mechanical durability | 20.000 cycles |
| Protection type (modular) | Magnetothermic switch |
| No. of poles | 3P |
| Modules (18 mm) | 3 |
| Network type | Alternating current (ac) |
| Trigger curve | C |
| Short circuit capacity | 6 kA |
| Fixation | 35mm DIN rail |
| Connection capacity | Up to 25 mm ² |
| Possibility of using pin type combs | Yes |
| Nominal current | 20A |
| Nominal voltage | 400 Vca - (50/60 Hz) |

Technical data

| | |
|-------------------------------|----------------|
| Fire resistance (GWEPT) | 960 °C |
| Ambient operating temperature | -5 °C ; +40 °C |
| Free of halogens | Yes |

Regulations

| | |
|--|---------------------|
| CE marking | Yes |
| CMim marking | Yes |
| According to Regulations UNE/EN | UNE-EN 60898-1:2020 |
| In accordance with the Low Voltage Electrotechnical Regulations (REBT) | Yes |
| AENOR certificate | Yes |
| According to European Directive 2014/35 / EU. Low voltage directive | Yes |

Sustainability

| | |
|--|-----------------------|
| According to European Directive 2011/65/UE (RoHS) | Yes |
| According to European Directive 2012/19/UE (RAEE2) | Yes |
| According to Regulations (RoHS) | UNE-EN IEC 63000:2022 |

Logistics and packaging

| | |
|---------------------------|----------------|
| Unit EAN code | 8423220287457 |
| EAN code container | 8423220287013 |
| EAN code packaging | 18423220287010 |
| Units packaging | 4 |
| Units carton | 40 |
| Pallet Units | 3600 |
| Packaging Measurements cm | 22x8,5x8 |
| Packaging Measures cm | 47x24x18 |
| Unit weight (g) | 286,2 |
| Container Weight (Kg) | 1,2148 |
| Packaging Weight (Kg) | 12,633 |
| Tariff code | 85362010 |

Documentation and downloads



Assembly instructions (0.26MB)



Safety Information (0.38MB)