

## Miniature Circuit Breaker 4P, 40A. Breaking capacity 6kA. C curve.

Miniature Circuit Breaker 4P, 40A. Breaking capacity 6kA. C curve. 4 modules. 400V AC (50 - 60 Hz).



## Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanical durability	20.000 cycles
Protection type (modular)	Magnetothermic switch
No. of poles	4P
Modules (18 mm)	4
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	6 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm <sup>2</sup>
Possibility of using pin type combs	Yes
Nominal current	40A
Nominal voltage	400 Vca - (50/60 Hz)

## Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

## Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60898-1:2020 (versión corregida Febrero 2024).
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
AENOR certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

## Logistics and packaging

Unit EAN code	8423220287570
EAN code container	8423220287136
EAN code packaging	18423220287133
Units packaging	3
Units carton	30
Pallet Units	1500
Packaging Measurements cm	22x8,5x8
Packaging Measures cm	47x24x18
Unit weight (g)	386
Container Weight (Kg)	1,208
Packaging Weight (Kg)	12,5434
Tariff code	85362010

## Documentation and downloads



[Assembly instructions \(0.26MB\)](#)



[Safety Information \(0.38MB\)](#)

