

DAY/NIGHT Contactor

DAY/NIGHT Modular contactor 2P, 20A. 2NO contacts. Coil voltage 230Vac (50/60 Hz). 1 module, 0-AUTO-1



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Modular device type	Contactors
No. of poles	2P
Modules (18 mm)	1
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Contacts	2NO
Nominal current	20A
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes

According to Regulations UNE/EN	UNE EN 61095:2010
According to Regulations IEC	UNE-EN IEC 60947-4-1
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220273160
EAN code container	8423220273009
EAN code packaging	18423220273006
Units packaging	12
Units carton	120
Pallet Units	6000
Packaging Measurements cm	22x95x85
Packaging Measures cm	47x24x18
Unit weight (g)	122
Container Weight (Kg)	1,464
Packaging Weight (Kg)	14,99
Tariff code	85362010

Documentation and downloads



[Safety Information \(0.38MB\)](#)