

Protector MCB 2x40A + surges permanent. and transitory

Protector MCB 2x40A+ surge permanent and transitory. 230Vac (50 - 60 Hz). C curve. 15kA



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of poles	1P + N
Modules (18 mm)	4
Neutral position	Right
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	15 Ka
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm ²
Nominal current	40A
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-20 °C ; +70 °C
Free of halogens	Yes

Regulations

CE marking	Yes
------------	-----

UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013 ; UNE-EN 50550:2012; UNE-EN 60898-1:2020
According to Regulations IEC	IEC 61643-11
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220216983
EAN code container	8423220216983
EAN code packaging	18423220216980
Units packaging	1
Units carton	20
Pallet Units	999
Packaging Measures cm	10,2x14x12
Unit weight (g)	481
Container Weight (Kg)	0,481
Packaging Weight (Kg)	10,229
Tariff code	85362010

Documentation and downloads



Safety Information (0.38MB)