

Transient surge protector 600V DC Type 2

Transient surge protection device for DC installations, rated at 600V DC, Type 2, 3P configuration and 3-module format. Suitable for photovoltaic and direct current applications.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Protection type (modular)	Permanent surge protector
No. of poles	2P
Modules (18 mm)	2
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Nominal voltage	600Vdc

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 50550:2012
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
---	-----

According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

EAN code container	8423220288621
EAN code packaging	18423220288628
Units packaging	1
Units carton	50
Tariff code	85362010

Documentation and downloads

 Safety Information (0.38MB)