

## Transient surge protector 1200V DC Type 2

Transient surge protection device for DC installations, rated at 1200V DC, Type 2, 3P configuration and 3-module format. Suitable for photovoltaic and direct current applications.



## Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Protection type (modular)	Permanent surge protector
No. of poles	3P
Modules (18 mm)	3
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Nominal voltage	1200Vdc

## Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C

## Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 50550:2012
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes

According to European Directive 2014/35 /  
EU. Low voltage directive

Yes

## Sustainability

According to European Directive  
2011/65/UE (RoHS)

Yes

According to European Directive  
2012/19/UE (RAEE2)

Yes

According to Regulations (RoHS)

UNE-EN IEC 63000:2022

## Logistics and packaging

Unit EAN code 8423220283138

EAN code container 8423220283138

EAN code packaging 18423220283135

Units packaging 50

Units carton 5000

Pallet Units 0

Packaging Measurements cm 42x25x28

Packaging Measures cm 120x100x15

Unit weight (g) 252,8

Container Weight (Kg) 13,64

Packaging Weight (Kg) 1384

Tariff code 85362010

## Documentation and downloads



Safety Information (0.38MB)