S24GM6-3

Motor protection circuit breaker 4-6.3A

Motor protection circuit breaker with adjustment range 4-6.3A, featuring thermal, magnetic and phase-failure protection. Compact 2.5-module format for motor control applications.



Features

Common applications	Industrial environments (factories, warehouses, etc.)
Protection type (modular)	Motor guard
No. of poles	3P
Modules (18 mm)	2.5
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Nominal current	4 a 6,3 A
Nominal voltage	230/400 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60947-4-1:2021

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220288522
EAN code container	8423220288522
EAN code packaging	18423220288529
Units packaging	1
Units carton	50
Pallet Units	2500
Packaging Measurements cm	9,5x5x9
Packaging Measures cm	49x27x19
Unit weight (g)	251,8
Container Weight (Kg)	0,2698
Packaging Weight (Kg)	13,995
Tariff code	85362010

Documentation and downloads

Safety Information (0.38MB)