

## Motor protection circuit breaker 4–6.3A

Motor protection circuit breaker with adjustment range 4–6.3A, featuring thermal, magnetic and phase-failure protection. Compact 2.5-module format for motor control applications.



## Features

Common applications	Industrial environments (factories, warehouses, etc.)
Protection type (modular)	Motor guard
No. of poles	3P
Modules (18 mm)	2.5
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Nominal current	4 a 6,3 A
Nominal voltage	230/400 Vca - (50/60 Hz)

## Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

## Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60947-4-1:2021

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
--	-----

According to European Directive 2014/35 / EU. Low voltage directive	Yes
---	-----

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
---	-----

According to European Directive 2012/19/UE (RAEE2)	Yes
--	-----

According to Regulations (RoHS)	UNE-EN IEC 63000:2022
---------------------------------	-----------------------

## Logistics and packaging

Unit EAN code	8423220288522
---------------	---------------

EAN code container	8423220288522
--------------------	---------------

EAN code packaging	18423220288529
--------------------	----------------

Units packaging	1
-----------------	---

Units carton	50
--------------	----

Pallet Units	2500
--------------	------

Packaging Measurements cm	9,5x5x9
---------------------------	---------

Packaging Measures cm	49x27x19
-----------------------	----------

Unit weight (g)	251,8
-----------------	-------

Container Weight (Kg)	0,2698
-----------------------	--------

Packaging Weight (Kg)	13,995
-----------------------	--------

Tariff code	85362010
-------------	----------

## Documentation and downloads



Safety Information (0.38MB)