

Residual Current Circuit-Breaker 4P, 40A. Class A. Sensitivity 30 mA

Residual Current Circuit-Breaker 4P, 40A. Class A. Sensitivity 30 mA 4 modules. 400V AC (50 - 60 Hz). Breaking capacity 6kA.



Features

| | |
|-------------------------------------|---|
| Common applications | Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.) |
| Mechanical durability | 15.000 cycles |
| Protection type (modular) | Diferential switch |
| No. of poles | 3P + N |
| Modules (18 mm) | 4 |
| Neutral position | Left |
| Network type | Alternating current (ac) |
| Sensitivity (Leakage current) | 30 mA |
| Short circuit capacity | 6 kA |
| Protection type | Class A |
| Delay type | Instant (No delay) |
| Fixation | 35mm DIN rail |
| Connection capacity | Up to 35 mm ² |
| Possibility of using pin type combs | Yes |
| Nominal current | 40A |
| Nominal voltage | 400 Vca - (50/60 Hz) |

Technical data

| | |
|-------------------------------|----------------|
| Fire resistance (GWEPT) | 960 °C |
| Ambient operating temperature | -5 °C ; +40 °C |

| | |
|------------------|-----|
| Free of halogens | Yes |
|------------------|-----|

Regulations

| | |
|--|---|
| CE marking | Yes |
| UK marking | Yes |
| CMim marking | Yes |
| According to Regulations UNE/EN | UNE-EN 61008-1:2013;UNE-EN IEC 61543:2023 |
| In accordance with the Low Voltage Electrotechnical Regulations (REBT) | Yes |
| AENOR certificate | Yes |
| CB certificate | Yes |
| According to European Directive 2014/35 / EU. Low voltage directive | Yes |

Sustainability


| | |
|--|-----------------------|
| According to European Directive 2011/65/UE (RoHS) | Yes |
| According to European Directive 2012/19/UE (RAEE2) | Yes |
| According to Regulations (RoHS) | UNE-EN IEC 63000:2022 |
| According to European Directive 2014/30/UE. (CEM) | Yes |

Logistics and packaging

| | |
|---------------------------|----------------|
| Unit EAN code | 8423220093669 |
| EAN code container | 8423220093669 |
| EAN code packaging | 18423220093666 |
| Units packaging | 1 |
| Units carton | 30 |
| Pallet Units | 4000 |
| Packaging Measurements cm | 9x4x8 |
| Packaging Measures cm | 47x43x18 |
| Unit weight (g) | 191 |

| | |
|-----------------------|----------|
| Container Weight (Kg) | 0,209 |
| Packaging Weight (Kg) | 6,884 |
| Tariff code | 85362010 |

Sketch



Documentation and downloads



Assembly instructions (0.26MB)



Safety Information (0.38MB)



Certificate (0.72MB)