

## Residual current circuit breaker 2P 40A 300mA Class A

Residual current circuit breaker 2P for electrical installations, rated at 40A, Class A and 300mA sensitivity. 2 modules, 230Vac (50 - 60 Hz) and 6kA breaking capacity for safe leakage protection.



### Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanical durability	15.000 cycles
Protection type (modular)	Diferential switch
No. of poles	1P + N
Modules (18 mm)	2
Neutral position	Left
Network type	Alternating current (ac)
Sensitivity (Leakage current)	300 mA
Short circuit capacity	6 kA
Protection type	Class A
Delay type	Instant (No delay)
Fixation	35mm DIN rail
Connection capacity	Up to 35 mm <sup>2</sup>
Possibility of using pin type combs	Yes
Nominal current	40A
Nominal voltage	230 Vca - (50/60 Hz)

### Technical data

Fire resistance (GWEPT)	960 °C
-------------------------	--------

Ambient operating temperature -5 °C ; +40 °C

## Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61008-1:2013 UNE-EN IEC 61543:2023
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022
According to European Directive 2014/30/UE. (CEM)	Yes

## Logistics and packaging

Unit EAN code	8423220282674
EAN code container	8423220283107
EAN code packaging	18423220283104
Units packaging	6
Units carton	60
Pallet Units	3000
Packaging Measurements cm	22x8,5x8
Packaging Measures cm	47x24x18
Unit weight (g)	172
Container Weight (Kg)	1,082
Packaging Weight (Kg)	11,165

Tariff code

85362010

---

## Documentation and downloads



Assembly instructions (0.26MB)



Safety Information (0.38MB)