

Residual current circuit breaker 4P 25A 30mA Class A

Residual current circuit breaker 4P for electrical installations, rated at 25A, Class A and 30mA sensitivity. 4 modules, 400Vac (50 – 60 Hz) and 6kA breaking capacity for safe leakage protection.



Features

| | |
|-------------------------------------|---|
| Common applications | Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.) |
| Mechanical durability | 15.000 cycles |
| Protection type (modular) | Diferential switch |
| No. of poles | 3P + N |
| Modules (18 mm) | 4 |
| Neutral position | Left |
| Network type | Alternating current (ac) |
| Sensitivity (Leakage current) | 30 mA |
| Short circuit capacity | 6 kA |
| Protection type | Class A |
| Delay type | Instant (No delay) |
| Fixation | 35mm DIN rail |
| Connection capacity | Up to 35 mm ² |
| Possibility of using pin type combs | Yes |
| Nominal current | 25A |
| Nominal voltage | 400 Vca - (50/60 Hz) |

Technical data

| | |
|-------------------------|--------|
| Fire resistance (GWEPT) | 960 °C |
|-------------------------|--------|

Ambient operating temperature -5 °C ; +40 °C

Regulations

| | |
|--|--|
| CE marking | Yes |
| CMim marking | Yes |
| According to Regulations UNE/EN | UNE-EN 61008-1:2013 UNE-EN IEC 61543:2023 |
| In accordance with the Low Voltage Electrotechnical Regulations (REBT) | Yes |
| According to European Directive 2014/35 / EU. Low voltage directive | Yes |

Sustainability

| | |
|--|-----------------------|
| According to European Directive 2011/65/UE (RoHS) | Yes |
| According to European Directive 2012/19/UE (RAEE2) | Yes |
| According to Regulations (RoHS) | UNE-EN IEC 63000:2022 |
| According to European Directive 2014/30/UE. (CEM) | Yes |

Logistics and packaging

| | |
|--------------------|----------------|
| Unit EAN code | 8423220288768 |
| EAN code container | 8423220287839 |
| EAN code packaging | 18423220287836 |
| Units packaging | 3 |
| Units carton | 30 |

Documentation and downloads



[Assembly instructions \(0.26MB\)](#)



[Safety Information \(0.38MB\)](#)