

## RCCB 4P 40A 300 mA Class A

Four-pole RCCB for three-phase installations, rated at 40A, Class A and 300 mA sensitivity. 4-module format, 400V AC and 6kA breaking capacity for dependable leakage protection.



## Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanical durability	15.000 cycles
Protection type (modular)	Diferential switch
No. of poles	3P + N
Modules (18 mm)	4
Neutral position	Left
Network type	Alternating current (ac)
Sensitivity (Leakage current)	300 mA
Short circuit capacity	6 kA
Protection type	Class A
Delay type	Instant (No delay)
Fixation	35mm DIN rail
Connection capacity	Up to 35 mm <sup>2</sup>
Possibility of using pin type combs	Yes
Nominal current	40A
Nominal voltage	400 Vca - (50/60 Hz)

## Technical data

Fire resistance (GWEPT)	960 °C
-------------------------	--------

Ambient operating temperature -5 °C ; +40 °C

## Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61008-1:2013 UNE-EN IEC 61543:2023
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022
According to European Directive 2014/30/UE. (CEM)	Yes

## Logistics and packaging

Unit EAN code	8423220288805
EAN code container	8423220287877
EAN code packaging	18423220287874
Units packaging	1
Units carton	1
Pallet Units	1
Packaging Measures cm	47x35x18
Unit weight (g)	1710,8
Container Weight (Kg)	1,7108
Packaging Weight (Kg)	2,4308
Tariff code	85362010

## Documentation and downloads



Assembly instructions (0.26MB)



Safety Information (0.38MB)