

RCCB 2P 40A 30 mA Class B

Residual current circuit breaker 2P for electrical installations, rated at 40A, Class B and 30 mA sensitivity. 2-module format, 230V AC (50/60 Hz) and 10kA breaking capacity.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanical durability	15.000 cycles
Protection type (modular)	Diferential switch
No. of poles	1P + N
Modules (18 mm)	2
Neutral position	Left
Network type	Alternating current (ac)
Sensitivity (Leakage current)	30 mA
Short circuit capacity	10 kA
Protection type	Class B
Delay type	Instant (No delay)
Fixation	35mm DIN rail
Connection capacity	Up to 35 mm²
Possibility of using pin type combs	Yes
Nominal current	40A
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C

Regulations

CE marking	Yes
------------	-----

CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61008-1:2013 UNE-EN IEC 61543:2023
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022
According to European Directive 2014/30/UE. (CEM)	Yes

Logistics and packaging

Unit EAN code	8423220288836
EAN code container	8423220287907
EAN code packaging	18423220287904
Units packaging	6
Units carton	60

Documentation and downloads

 Assembly instructions (0.26MB)

 Safety Information (0.38MB)