

RCCB 4P 63A 30 mA Class A

Four-pole RCCB for three-phase installations, rated at 63A, Class A and 30 mA sensitivity. 4-module format, 400V AC and 6kA breaking capacity for dependable leakage protection.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanical durability	15.000 cycles
Protection type (modular)	Diferential switch
No. of poles	3P + N
Modules (18 mm)	4
Neutral position	Left
Network type	Alternating current (ac)
Sensitivity (Leakage current)	30 mA
Short circuit capacity	6 kA
Protection type	Class A
Delay type	Instant (No delay)
Fixation	35mm DIN rail
Connection capacity	Up to 35 mm ²
Possibility of using pin type combs	Yes
Nominal current	63A
Nominal voltage	400 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
-------------------------	--------

Ambient operating temperature	-5 °C ; +40 °C
-------------------------------	----------------

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61008-1:2013 UNE-EN IEC 61543:2023
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022
According to European Directive 2014/30/UE. (CEM)	Yes

Logistics and packaging

Unit EAN code	8423220282698
EAN code container	8423220283121
EAN code packaging	18423220283128
Units packaging	3
Units carton	30
Pallet Units	3000
Packaging Measurements cm	22x8,5x8
Packaging Measures cm	47x24x18
Unit weight (g)	303,4
Container Weight (Kg)	0,9602
Packaging Weight (Kg)	9,947

Tariff code	85362010
-------------	----------

Documentation and downloads

 Assembly instructions (0.26MB)

 Safety Information (0.38MB)