

Home protection kit with RCCB and MCBs

Home protection kit for residential electrical panels including: 1 RCCB 1P+N 40A-30mA, AC class 1 MCB 2P 25A, C curve, 6kA (main switch) 1 MCB 1P+N 10A, C curve, 6kA 5 MCB 1P+N 16A, C curve, 6kA 1 MCB 1P+N 25A, C curve, 6kA.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Mechanical durability	15.000 cycles
Protection type (modular)	Differential switch + circuit breaker.
Modules (18 mm)	18
Neutral position	Left
Network type	Alternating current (ac)
Trigger curve	C
Sensitivity (Leakage current)	30 mA
Short circuit capacity	6 kA
Protection type	Class AC
Delay type	Instant (No delay)
Fixation	35mm DIN rail
Connection capacity	Up to 35 mm ²
Possibility of using pin type combs	Yes
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
------------	-----

CMim marking	Yes
According to Regulations	UNE-EN 60898-1:2020
According to Regulations UNE/EN	UNE-EN 61008-1:2013;UNE-EN IEC 61543:2023
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
CB certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to European Directive 2014/30/UE. (CEM)	Yes

Logistics and packaging

Unit EAN code	8423220287174
EAN code container	8423220287174
EAN code packaging	18423220287171
Units packaging	1
Units carton	10
Pallet Units	480
Packaging Measures cm	47x35x18
Unit weight (g)	1710,8
Container Weight (Kg)	1,7136
Packaging Weight (Kg)	17,806
Tariff code	85362010

Documentation and downloads



Safety Information (0.38MB)