

Disconnect fuse holder 10x38 size O

Disconnect fuse holder size O for 10x38 cylindrical fuse, 1P, 500V and up to 32A. Compact solution for protection, isolation and maintenance in electrical panels.



Features

Common applications	Industrial environments (factories, warehouses, etc.)
Protection type (modular)	Fuse holder
No. of poles	1P
Modules (18 mm)	1
Network type	Alternating current (ac)
Short circuit capacity	20kA
Fixation	35mm DIN rail
Fuse size	Size O (10x38 mm)
Nominal current	32A
Nominal voltage	690 Vca (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
------------	-----

UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60269-1:2008
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220290044
EAN code container	8423220289703
EAN code packaging	18423220289700
Units packaging	12
Units carton	200
Tariff code	85362010

Documentation and downloads



Assembly instructions (0.9MB)



Safety Information (0.38MB)