S24CM4A63

Modular contactor 4P 63A 4NO



Modular contactor 4P, 63A, 4NO contacts and 3-module format. Coil voltage 230V~ and rated voltage 240/415V AC (50/60 Hz).

Features

Common applications	Industrial environments (factories, warehouses, etc.)
Modular device type	Contactor
No. of poles	4P
Modules (18 mm)	3
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Contacts	4NO
Nominal current	63A
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

According to Regulations UNE/EN	UNE-EN 60947-4-1:2021
According to Regulations IEC	IEC 61095:2009
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220289512
EAN code container	8423220288584
EAN code packaging	18423220288581
Units packaging	4
Units carton	40
Pallet Units	1000
Packaging Measurements cm	22x8,5x8
Packaging Measures cm	47x24x18
Unit weight (g)	175
Container Weight (Kg)	0,75
Packaging Weight (Kg)	7,845
Tariff code	85362010

Documentation and downloads

Safety Information (0.38MB)