

Transient surge protector T1+T2 1P+N

Transient surge protection device Type 1+2 for single-phase lines, with 1P+N configuration, 320V AC, 12.5–20–50kA discharge capacity and 2-module format.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Protection type (modular)	Transient surge protector
No. of poles	1P + N
Modules (18 mm)	2
Network type	Alternating current (ac)
Protection type	Class AC
Fixation	35mm DIN rail

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013
According to Regulations IEC	IEC- 61643-11:2011

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

EAN code container	8423220288492
EAN code packaging	18423220288499
Units packaging	1
Units carton	86
Tariff code	85362010

Documentation and downloads

 Safety Information (0.38MB)