

Transient surge protector 1200V DC Type 2

Transient surge protection device for DC installations, rated at 1200V DC, Type 2, 3P configuration and 3-module format. Suitable for photovoltaic and direct current applications.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Protection type (modular)	Permanent surge protector
No. of poles	3P
Modules (18 mm)	3
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Nominal voltage	1200Vdc

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 50550:2012
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes

According to European Directive 2014/35 / EU. Low voltage directive	Yes
---	-----

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220283138
EAN code container	8423220283138
EAN code packaging	18423220283135
Units packaging	50
Units carton	5000
Pallet Units	0
Packaging Measurements cm	42x25x28
Packaging Measures cm	120x100x15
Unit weight (g)	252,8
Container Weight (Kg)	13,64
Packaging Weight (Kg)	1384
Tariff code	85362010

Documentation and downloads



Safety Information (0.38MB)