

Transient surge protector T2 3P+N

Transient surge protection device Type 2 for three-phase lines, with 3P+N configuration, 320V AC, 15–30kA discharge capacity and 2-module format.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Protection type (modular)	Transient surge protector
No. of poles	3P + N
Modules (18 mm)	2
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013
According to Regulations IEC	IEC- 61643-11:2011

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220288485
EAN code container	8423220288485
EAN code packaging	18423220288482
Units packaging	1
Units carton	45
Pallet Units	2250
Packaging Measurements cm	10x7,5x7,5
Packaging Measures cm	42x25x16
Unit weight (g)	228
Container Weight (Kg)	0,2468
Packaging Weight (Kg)	11,511
Tariff code	85362010

Documentation and downloads



Safety Information (0.38MB)