

Transient surge protector T1+T2 3P+N

Transient surge protection device Type 1+2 for three-phase lines, with 3P+N configuration, 320V AC, 12.5–20–50kA discharge capacity and 4-module format.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Protection type (modular)	Transient surge protector
No. of poles	3P + N
Modules (18 mm)	4
Network type	Alternating current (ac)
Protection type	Class AC
Fixation	35mm DIN rail

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013
According to Regulations IEC	IEC- 61643-11:2011

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
--	-----

According to European Directive 2014/35 / EU. Low voltage directive	Yes
---	-----

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
---	-----

According to European Directive 2012/19/UE (RAEE2)	Yes
--	-----

According to Regulations (RoHS)	UNE-EN IEC 63000:2022
---------------------------------	-----------------------

Logistics and packaging

EAN code container	8423220288508
--------------------	---------------

EAN code packaging	18423220288505
--------------------	----------------

Units packaging	1
-----------------	---

Units carton	1
--------------	---

Pallet Units	1
--------------	---

Packaging Measures cm	47x35x18
-----------------------	----------

Unit weight (g)	1710,8
-----------------	--------

Container Weight (Kg)	1,7108
-----------------------	--------

Packaging Weight (Kg)	2,4308
-----------------------	--------

Tariff code	85362010
-------------	----------

Documentation and downloads



Safety Information (0.38MB)