

MCB protector 2x50A with permanent and transient OVP

Combined MCB protector with permanent and transient overvoltage protection, rated at 2x50A, C curve and 10kA breaking capacity. 4-module format for 230V AC installations (50/60 Hz).



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
No. of poles	2P
Modules (18 mm)	4
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	10 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm ²
Nominal current	50A
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-20 °C ; +70 °C

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013 ; UNE-EN 50550:2012; UNE-EN 60898-1:2020

According to Regulations IEC	IEC 61643-11
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220288652
EAN code container	8423220288652
EAN code packaging	18423220288659
Units packaging	1
Units carton	30
Pallet Units	0
Packaging Measures cm	0x0x0
Unit weight (g)	0
Container Weight (Kg)	0
Packaging Weight (Kg)	0
Tariff code	85362010

Documentation and downloads



Safety Information (0.38MB)