

Undervoltage release for MCBs, AC 230V supply and 1-module format.

Undervoltage release accessory for MCBs, with AC 230V supply and 1-module format. Designed to trip the device when supply voltage drops.



Features

Common applications	Industrial environments (factories, warehouses, etc.)
Protection type (modular)	Minimum tension coil
No. of poles	1P + N
Modules (18 mm)	1
Neutral position	Right
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Nominal voltage	230 Vca - (50/60 Hz)
Compatibility	S24M..
Union mode	Engageable
Identify option	Yes

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C

Regulations

CE marking	Yes
------------	-----

CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60947-5-1:2018
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220282544
EAN code container	8423220283046
EAN code packaging	18423220283043
Units packaging	8
Units carton	80
Pallet Units	4000
Packaging Measurements cm	22x8,5x8
Packaging Measures cm	47x24x18
Unit weight (g)	63,4
Container Weight (Kg)	0,5572
Packaging Weight (Kg)	5,917
Tariff code	85362010

Documentation and downloads



[Safety Information \(0.38MB\)](#)