CLC16

Connecteur pour câble rigide et souple pour les sections de 0,5 à 6 mm²

Connecteur pour câble rigide et souple pour les sections de 0,5 à 6 mm². Red - yellow colours. Bag 6 units.



Features

Type	Connector
Flexible cable minimum section	0,5 mm²
Flexible cable maximum section	6 mm²
Minimum rigid cable section	0,5 mm²
Rigid cable maximum section	6 mm²

Technical data

Fire resistance (GWEPT)	850 ºC
Heat resistance (Ball pressure)	125 ºC
Work stress	400 Vca
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60998-1:2005
According to REBT	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220088368
EAN code container	8423220065284
EAN code packaging	18423220065281
Units packaging	10
Units carton	320
Pallet Units	11200
Packaging Measurements cm	9x19x7
Packaging Measures cm	59,5x20x37,5
Unit weight (g)	26
Container Weight (Kg)	0,32
Packaging Weight (Kg)	10,66
Tariff code	85369010