Cable extension with 6 sockets 2P+E, 16A 250V~. 1,5 m of cable.

Cable extension with 6 sockets 2P+E, 16A 250V~. 1,5 m of cable.MAX. 3680W. Cable H05VV-F 3G1,5mm². With fixing holes to the wall. Inputs for 7x12, 10x16, 10x20 and 12x12 mm mini-trunking.
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Type	Multiple base
No. of bases	6
Basic characteristics	2P+E, 16A 250V~
Cable length	1,5 m.
Maximum power	3.680 W
Cable	Yes
Cable Features	H05VV-F 3G1,5mm²
Possibility of using KIT-DIN35	Yes
Wall fixing holes	Yes

Technical data

Protection Degree (IP)	IP20
Fire resistance (GWEPT)	850 ºC
Heat resistance (Ball pressure)	125 ºC
Ambient operating temperature	-5 ºC ; +60 ºC

Regulations

CE marking	Yes
According to Regulations UNE/EN	UNE-20315-1-1:2017; UNE-20315-1-2:2017

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes


Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220901629
EAN code container	8423220901629
EAN code packaging	18423220901626
Units packaging	1
Units carton	30
Pallet Units	1050
Packaging Measurements cm	36,6x7x20
Packaging Measures cm	59,5x20x37,5
Unit weight (g)	483
Container Weight (Kg)	0,50
Packaging Weight (Kg)	15,56
Tariff code	85366990

Sketch



Documentation and downloads

Assembly instructions (0.74MB)

Certificate (0.3MB)

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com