8005IL

Multiple socket of 5 sockets 2P+E, 16A 250V~. With light switch.

Multiple socket of 5 sockets 2P+E, 16A 250V~. With light switch.MAX. 3680W. White colour. Easy connection access. With fixing holes to the wall. Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Type	Multiple base
No. of bases	5
Basic characteristics	2P+E, 16A 250V~
Maximum power	3.680 W
Light switch	Yes
Terminal system	Screw connection
Possibility of using hanger	Yes
Possibility of using KIT-DIN35	Yes
Wall fixing holes	Yes

Technical data

Protection Degree (IP)	IP20
Fire resistance (GWEPT)	850 ºC
Heat resistance (Ball pressure)	125 ºC
Ambient operating temperature	-5 ºC ; +60 ºC
Free of halogens	Yes

Regulations

CE marking	Yes
According to Regulations UNE/EN	UNE-20315-1-1:2017; UNE-20315-1-2:2017
According to REBT	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

Intertek certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes


Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220237537
EAN code container	8423220063815
EAN code packaging	18423220063812
Units packaging	10
Units carton	40
Pallet Units	1600
Packaging Measurements cm	26,3x10,3x20,4
Packaging Measures cm	43,4x33x22,5
Unit weight (g)	234
Container Weight (Kg)	0,37
Packaging Weight (Kg)	10,50
Tariff code	85366990

Sketch



Documentation and downloads

Assembly instructions (0.74MB)

Certificate (0.33MB)

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com