706TK

Plug 2P+E , 16A 250V~. Black rubber.



Plug 2P+E , 16A 250V~. Black rubber. With cable gland. With double earth system. IP54

Features

Common applications	Domestic / tertiary outdoor environment (garden, swimming pool, parking, public road, etc.)
Material	Rubber
Type	Plug
No. of poles	2P + T
Type of terminal connection	Screw connection
Nominal current	16A
Grounding	Double system
Folding cable tie to facilitate connection	Yes
PPossibility to use 3x2.5mm² cable	Yes
Nominal current	16A
Nominal voltage	250V~
Color	Black-blue

Technical data

Fire resistance (GWEPT)	650/750 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes

According to Regulations UNE/EN	UNE-20315-1-1:2017; UNE-20315-1-2:2017
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
In accordance with the Regulation (EU) 2023/988 of the European Parliament and of the Council on general product safey	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220254695
EAN code container	8423220254060
EAN code packaging	18423220254067
Units packaging	13
Units carton	208
Pallet Units	7280
Packaging Measurements cm	14,5x8,8x19
Packaging Measures cm	59,5x37,5x20
Unit weight (g)	54,6
Container Weight (Kg)	0,7568
Packaging Weight (Kg)	12,6488
Tariff code	85366990

Documentation and downloads

Assembly instructions (2.79MB)

Commercial doc. (0.87MB)

Safety Information (0.38MB)

BYCLA , plugs and sockets made in Spain (Solera)