

## Plug 2P+E , 16A 250V~. White elastomer

Plug 2P+E , 16A 250V~. White elastomer. Folding cable clamp for easy connection. With double earth system. IP20



### Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Material	Elastomer.
Type	Plug
No. of poles	2P + T
Type of terminal connection	Screw connection
Nominal current	16A
Grounding	Double system
Folding cable tie to facilitate connection	Yes
PPossibility to use 3x2.5mm <sup>2</sup> cable	Yes
Nominal current	16A
Nominal voltage	250V~
Color	White-blue

### Technical data

Fire resistance (GWEPT)	650/750 °C
Heat resistance (Ball pressure)	70/125 °C
Free of halogens	Yes

### Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-20315-1-1:2017; UNE-20315-1-2:2017

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
--	-----

In accordance with the Regulation (EU) 2023/988 of the European Parliament and of the Council on general product safety	Yes
---	-----

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
---	-----

According to European Directive 2012/19/UE (RAEE2)	Yes
--	-----

According to Regulations (RoHS)	UNE-EN IEC 63000:2022
---------------------------------	-----------------------

## Logistics and packaging

Unit EAN code	8423220095700
---------------	---------------

EAN code container	8423220095694
--------------------	---------------

EAN code packaging	18423220095691
--------------------	----------------

Units packaging	20
-----------------	----

Units carton	320
--------------	-----

Pallet Units	11200
--------------	-------

Packaging Measurements cm	14,5x8,8x19
---------------------------	-------------

Packaging Measures cm	59,5x37,5x20
-----------------------	--------------

Unit weight (g)	39
-----------------	----

Container Weight (Kg)	0,827
-----------------------	-------

Packaging Weight (Kg)	14,0456
-----------------------	---------

Tariff code	85366990
-------------	----------

## Documentation and downloads



Commercial doc. (0.27MB)



Safety Information (0.38MB)