707CF

Mobile socket 2P+E, (FR) 16A 250V~. Black rubber.



Mobile socket 2P+E, (FR) 16A 250V~. Earth system (French. Black rubber.Folding cable clamp for easy connection.

Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Material	Rubber
Type	Mobile socket
No. of poles	2P + T
Type of terminal connection	Screw connection
Nominal current	16A
Grounding	French system
Folding cable tie to facilitate connection	Yes
PPossibility to use 3x2.5mm² cable	Yes
Nominal current	16A
Nominal voltage	250V~
Color	Black-blue

Technical data

Fire resistance (GWEPT)	650/750 °C
Heat resistance (Ball pressure)	70/125 °C
UV resistance	Yes
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes

Portalámparas y Accesorios Solera S.A.U. Pol. Ind. Fuente del Jarro C/ Villa de Madrid, 53 46988 Paterna (Valencia) España
+34 961 322 301 | solera@psolera.com | www.psolera.com

According to Regulations	NF C61-314
According to Regulations UNE/EN	UNE-20315-1-1:2017; UNE-20315-1-2:2017
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
In accordance with the Regulation (EU) 2023/988 of the European Parliament and of the Council on general product safey	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220247789
EAN code container	8423220247772
EAN code packaging	18423220247779
Units packaging	24
Units carton	192
Pallet Units	6720
Packaging Measurements cm	14,5x8,8x19
Packaging Measures cm	59,5x37,5x20
Unit weight (g)	59
Container Weight (Kg)	1,4801
Packaging Weight (Kg)	12,3808
Tariff code	85366990

Documentation and downloads

Commercial doc. (0.27MB)

Safety Information (0.38MB)