

Angled industrial flush socket 3P+N+E, 63A 400V~. IP44.

Flush-mount industrial base with angled design, featuring 3 poles + neutral + earth, rated at 63A 400V~. IP44 protection allows use in industrial environments with occasional dust or splashes. The inclined design ensures ergonomic plug connection, ideal for high-power panels and demanding equipment.



Features

Common applications	Industrial environments (factories, warehouses, etc.)
Type	Fitted socket outlet
No. of poles	3P + N + T
Type of terminal connection	Screw connection
Earth position	6h
Frame for Indubox	MR1332
Nominal current	63A
Nominal voltage	400V
Color	Red

Technical data

Protection Degree (IK)	IK09
Impact shock resistance	Strong
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	125 °C
Ambient operating temperature	-5 °C ; +40 °C
Dimensional stability	-25 °C -> +80 °C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60309-1:2023 UNE-EN 60309-2:2023
In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes


Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Logistics and packaging

Unit EAN code	8423220089648
EAN code container	8423220089648
EAN code packaging	18423220089645
Units packaging	1
Units carton	2
Pallet Units	99999
Packaging Measures cm	29x19x23
Unit weight (g)	213,8
Container Weight (Kg)	0,2138
Packaging Weight (Kg)	0,5986
Tariff code	85366990

Sketch



Ampere	63		
Pole	3	4	5
a [mm]	100	100	100
b [mm]	112	112	112
c [mm]	80	80	80
d [mm]	88	88	88
e [mm]	64	64	64
f [mm]	74	74	74
g [mm]	92	92	92
h [mm]	82	82	82
i [mm]	7	7	7
j [mm]	132	132	132
k [mm]	146	146	146



Documentation and downloads



Safety Information (0.38MB)